SPECIFICATION KOZ TYPE B-TOOL L

Application: The KOZ B-tool L is the tool to assemble KOZ cable clamps and blocks on a straight or

round pole, without damaging them by e.g. drilling or sawing. The KOZ B-tool L can also

be used to install other products on straight or round poles.

Range: B-tool L is suitable for:

KOZ ST 75-100, 100-130, 120-160 KOZ STC 72-100, 100-130, 120-160

KOZ TRI eco 67-82

KOZ TRI 25-40, 38-53, 53-66, 67-82, 82-98

Material: Black polyamide (PA66), fibreglass-reinforced, virgin material.

Fire resistance: UL94 V-0 and classification standard EN 45545-2: 2020 – Railway applications.

Requirement set R22,R23 / Hazard level HL1,HL2.

Temperature: Permanent application from -80°C to +120°C. Short-term heating of up to +220°C.

Advantages: Resistant to oils, greases, frost, heat, UV, ozone, salt water, salts, acids

and aggressive chemicals.

Non-oxidizing, non-corrosive, non-magnetic and non-conductive.

Halogen-free and no sharp edges.


Lifetime warranty, easy assembly and available worldwide.

Extra possibilities: B-tools can be assembled by using a steel tie ("Bandit band"). You can turn the B-tool

inside or outside, depending on the outer diameter of the cable.







DIMENSIONS IN MILIMETERS

Туре	L	В		D	S	Н
KOZ B-tool L	80	42	14,5	6	40-2	34