## **SPECIFICATION KOZ TYPE B-TOOL S**

**Application:** The KOZ B-tool S is the tool to assemble KOZ cable clamps and blocks on a straight or

round pole, without damaging them by e.g. drilling or sawing. The KOZ B-tool S can also

be used to install other products on straight or round poles.

Range: B-tool S is suitable for:

KOZ ST 11-17, 18-26, 26-38, 36-52, 50-75

KOZ STC 21-38, 36-52, 46-75 KOZ TRI eco 24-35, 33-46, 47-66

KOZ UNI 3x 13-32, 4x 13-32, 3x 30-49, 4x 30-49, 3x 45-67

KOZ TRI UNI 3x3 27-37, 4x3 27-37

KOZ SQ 28, 25-35

**Material:** Black polyamide (PA66), fibreglass-reinforced, virgin material.

Fire resistance: UL94 V-0 and classification standard EN 45545-2: 2020 – Railway applications.

Requirement set R22,R23 / Hazard level HL1,HL2.

**Temperature:** Permanent application from -80°C to +120°C. Short-term heating of up to +220°C.

Advantages: Resistant to oils, greases, frost, heat, UV, ozone, salt water, salts, acids

and aggressive chemicals.

Non-oxidizing, non-corrosive, non-magnetic and non-conductive.

Halogen-free and no sharp edges.


Lifetime warranty, easy assembly and available worldwide.

Extra possibilities: B-tools can be assembled by using a steel tie ("Bandit band"). You can turn the B-tool

inside or outside, depending on the outer diameter of the cable.







## **DIMENSIONS IN MILIMETERS**

Туре	L	В	1	D	S	Н
KOZ B-tool S	60	35	12,5	5	26-2	32